


KENT HYDRA RAM 40GII



One of the largest models in the Kent Hydra Ram family, the 40G has all the muscle needed for heavy duty breaking tasks requiring up to 7,000 ft. lbs. of impact force. Designed for use on excavators, the 40G is ideally suited for such demanding breaking jobs as hard rock mining, heavy quarry work and bridge and road demolition. Like all Kent Hydra Rams, the 40G's simple, sophisticated design not only assures superior breaking performance, but ease of service, thanks to standard features like easily replaceable front head bushing and centrally arranged parts on the cylinder side for easy access and maintenance.

Features/Benefits

- Nitrogen charged back head for superior impact energy.
- Specially-designed piston for efficient transfer of energy to working steel.
- Blow frequency adjuster adapts tool and carrier to work conditions.
- Square breaker body encased by heavy-duty sideplates for maximum strength and rigidity.
- Innovative valve design suppresses hydraulic pulsation for operator comfort and carrier protection.
- Standard working steel of your choice with mounting pins at no additional charge.
- Underwater installation kits available.

| | |
|-------------------------|---------------------------------------------|
| Mounting Style | Top |
| Weight | 5990 lbs. (2717 kg) |
| Length (w/Brkt.) | 118 in. (2997 mm) |
| Blows/Minute (variable) | 300-600 |
| Impact Energy Class | 7000 ft/lbs (3175 kg/m) |
| Oil Flow | 50-66 GPM (190-250 LPM) |
| Operating Pressure | 2275-2550 PSI (160-180 kg/cm ²) |
| Tool Diameter | 6.25 in. (160 mm) |
| Usable Working Steel | 32.75 in. (832 mm) |



711 Lake Street • Kent, Ohio 44240
 216-673-5826 • Fax: 216-673-5824, Ext. 233
 Toll Free: 1-800-527-2282 (East Coast) • 1-800-624-1616 (West Coast)

