



B555/B999 AIR RAM SERIES

Air Rams are designed for skid-steer loaders, rubber-tired backhoes and hydraulic excavators. Ideal for use on roads and bridges, rock, utility applications and in steel mills for ladle and furnace cleaning where heat can be detrimental to hydraulic breakers. These hammers have proven themselves for more than two decades.

Features and Benefits:

- › Automatic valve provides maximum power with a minimum of air consumption
- › Piston impacts tappet not working steel, protecting the piston from damage
- › Air cushions reduce impact action of piston and tappet reducing wear and tear of critical internal parts

IMPACT ENERGY "CLASS"	B555-500 ft. lbs	B999-1000 ft. lbs
Weight in Lbs (kg)	502 (228)	950 (431)
Length in Inches (mm)		
Without Steel in (mm)	32.5 (826)	57 (1,448)
With Moil Point in (mm)	50 (1,270)	74 (1,880)
Bore in inches (mm)	3.75 (95)	4.62 (117)
Stroke in Inches (mm)	4.75 (121)	15 (381)
Working Steel Diameter in inches (mm)	2.5 (64)	3.5 (89)
Chuck Sizes in Inches (mm)	2.5 (64)	3.5 (89)
Optional	3.0 (96)	-
Air Hose Size in Inches (mm)	1 (26)	1.5 (38)
Blows Per Minute	600	600
Required CFM	175	250
Carrier Options		

CARRIER OPTIONS

SKIDSTEER

MINI

BACKHOE

EXCAVATOR



CORPORATE HEADQUARTERS
 711 Lake Street Kent, OH 44240
Ph: 330-673-5826
Fax: 330-677-1616
Toll Free: 1-800-527-2282

SOUTHEAST SALES AND SERVICE FACILITY
 155 Dexter Road
 Spartanburg, SC 29303
Ph: 864-541-0125

www.frdusa.com