



F35 Qt

Designed for excavators in the 28.5 to 35 ton range, the F35 Qt is a hard hitting hammer that has no rivals. With years of research behind each hammer, it's no accident the F-series outperforms the competition. It starts from the inside out with a patented dust intake prevention system that keeps critical internal parts free from the damage dirt can cause, and continues with the hydraulic safety valve that actuates when the maximum hydraulic pressure is exceeded. We don't stop there, a larger piston diameter and increase in the back head pressure improves the hammers impact performance. An optional hi-lo speed control actuated from the cab matches the hammer and carrier to the application. All Furukawa hammers come complete with Furukawa's exclusive Pro-Pak for ease of installation. The Pro-Pak includes hose whips, mounting hardware, standard working steel and tool kit with operating manual at no additional charge.

F35

Features and Benefits:

- ⇨ A patented dust intake prevention system prevents dust from entering the front head during the piston stroke. This improves the life of the piston as well as the working steel and bushings
- ⇨ A higher back head pressure and larger piston diameter results in a 20% increase in impact energy over previous models
- ⇨ An optional hi/lo speed control is available to match the hammer and carrier to the work at hand conveniently mounted in the cab
- ⇨ Built-in hydraulic safety valve actuates when the carrier exceeds the maximum pressure. This eliminates the need for a costly relief valve in the hydraulic system of the carrier
- ⇨ Qt design features reduced noise levels for use in city environments
- ⇨ Kits are available for underwater demolition



IMPACT ENERGY CLASS	6000 ft. lbs.
Weight in Lbs (kg)	5,328 (2,417)
Length in inches (mm)	121 (3,086)
Working Steel	
Diameter in inches (mm)	6 (150)
New length measured from fronthead (in)	30.50
Replaceable length measured from fronthead (in)	18.00
General Specifications	
Adjustable BPM	320 ~ 600
Acceptable GPM Range (LPM)	46 ~ 58 (175 ~ 220)
Acceptable PSI Range (Bar)	2,320 ~ 2,610 (160 ~ 180)
85 dB(A) Qt version@	16 - meters
Recommended Carrier in U.S. Tons	28.5 ~ 35
Carrier Options	■


Note: 1. Weight and length for all versions include working steel and "Universal" top cap.

All Furukawa hammers come complete with Furukawa's exclusive Pro-Pak for ease of installation. The Pro-Pak includes hose whips, mounting hardware, standard working steel, tool kit and operating manual at no additional charge.



CARRIER OPTIONS

EXCAVATOR



www.frdusa.com

CORPORATE HEADQUARTERS

711 Lake Street Kent, OH 44240
Ph: 330-673-5826
Fax: 330-677-1616
Toll Free: 1-800-527-2282

SOUTHEAST SALES AND SERVICE FACILITY

155 Dexter Road
 Spartanburg, SC 29303
Ph: 864-541-0125