


KENT HYDRA RAM 50GII



The largest model in the Kent Hydra Ram family, the 50G has all the muscle needed for heavy duty breaking tasks requiring up to 10,000 ft. lbs. of impact force. Designed for use on excavators, the 50G is ideally suited for such demanding breaking jobs as hard rock mining, heavy quarry work and bridge and road demolition. Like all Kent Hydra Rams, the 50G's simple, sophisticated design not only assures superior breaking performance, but ease of service, thanks to standard features like easily replaceable front head bushing and centrally arranged parts on the cylinder side for easy access and maintenance.

Features/Benefits

- Nitrogen charged back head for superior impact energy.
- Specially-designed piston for efficient transfer of energy to working steel.
- Blow frequency adjuster adapts tool and carrier to work conditions.
- Square breaker body encased by heavy-duty sideplates for maximum strength and rigidity.
- Innovative valve design suppresses hydraulic pulsation for operator comfort and carrier protection.
- Standard working steel of your choice with mounting pins at no additional charge.
- Underwater installation kits available.

Bracket Type	Top
Weight	8660 lbs (3928 kg)
Length (w/Brkt.)	136 in (3454 mm)
Blows/Minute (variable)	250/500
Impact Energy Class	10,000 ft/lbs (4536 kg/m)
Oil Flow	66-85 GPM (250-355 LPM)
Operating Pressure	2275-2550 PSI (160-180 KG)
Tool Dia	7 in (180 mm)
Usable Working Steel	34.75 in (883 mm)



711 Lake Street • Kent, Ohio 44240
216-673-5826 • Fax: 216-673-5824, Ext. 233
Toll Free: 1-800-527-2282 (East Coast) • 1-800-624-1616 (West Coast)

